


# RA Crossed Roller Bearings



| Выбрать запрос | запрос | Model No. | Major dimensions |                |                              |        |               | Shoulder dimensions |       | Basic load rating(radial) |      | Масса |       |
|----------------|--------|-----------|------------------|----------------|------------------------------|--------|---------------|---------------------|-------|---------------------------|------|-------|-------|
|                |        |           | Inner diameter   | Outer diameter | Roller pitch circle diameter | Ширина | Greasing hole | г (мин)             | дс    | Dh                        | C    | C0    | Масса |
|                |        |           | д:               | Д:             | dp                           | BB1    | а             | б                   |       |                           |      | кN    | кN    |
| RA5008         | 50     | 66        | 57               | 8              | 2                            | 0.8    | 0.5           | 53.5                | 60.5  | 5.1                       | 7.19 | 0.08  |       |
| RA6008         | 60     | 76        | 67               | 8              | 2                            | 0.8    | 0.5           | 63.5                | 70.5  | 5.68                      | 8.68 | 0.09  |       |
| RA7008         | 70     | 86        | 77               | 8              | 2                            | 0.8    | 0.5           | 73.5                | 80.5  | 5.98                      | 9.8  | 0.1   |       |
| RA8008         | 80     | 96        | 87               | 8              | 2                            | 0.8    | 0.5           | 83.5                | 90.5  | 6.37                      | 11.3 | 0.11  |       |
| RA9008         | 90     | 106       | 97               | 8              | 2                            | 0.8    | 0.5           | 93.5                | 100.5 | 6.76                      | 12.4 | 0.12  |       |
| RA10008        | 100    | 116       | 107              | 8              | 2                            | 0.8    | 0.5           | 103.5               | 110.5 | 7.15                      | 13.9 | 0.14  |       |
| RA11008        | 110    | 126       | 117              | 8              | 2                            | 0.8    | 0.5           | 113.5               | 120.5 | 7.45                      | 15   | 0.15  |       |
| RA12008        | 120    | 136       | 127              | 8              | 2                            | 0.8    | 0.5           | 123.5               | 130.5 | 7.84                      | 16.5 | 0.17  |       |
| RA13008        | 130    | 146       | 137              | 8              | 2                            | 0.8    | 0.5           | 133.5               | 140.5 | 7.94                      | 17.6 | 0.18  |       |
| RA14008        | 140    | 156       | 147              | 8              | 2                            | 0.8    | 0.5           | 143.5               | 150.5 | 8.33                      | 19.1 | 0.19  |       |
| RA15008        | 150    | 166       | 157              | 8              | 2                            | 0.8    | 0.5           | 153.5               | 160.5 | 8.82                      | 20.6 | 0.2   |       |
| RA16013        | 160    | 186       | 172              | 13             | 2.5                          | 1.6    | 0.8           | 165                 | 179   | 23.3                      | 44.9 | 0.59  |       |
| RA17013        | 170    | 196       | 182              | 13             | 2.5                          | 1.6    | 0.8           | 175                 | 189   | 23.5                      | 46.5 | 0.64  |       |
| RA18013        | 180    | 206       | 192              | 13             | 2.5                          | 1.6    | 0.8           | 185                 | 199   | 24.5                      | 49.8 | 0.68  |       |
| RA19013        | 190    | 216       | 202              | 13             | 2.5                          | 1.6    | 0.8           | 195                 | 209   | 24.9                      | 51.5 | 0.69  |       |
| RA20013        | 200    | 226       | 212              | 13             | 2.5                          | 1.6    | 0.8           | 205                 | 219   | 25.8                      | 54.7 | 0.71  |       |