

## XU crossed roller slewing bearing

Выбрать	запрос	Identification number	Main dimensions								load rating		Basic load rating		weight
			inner ring	outer ring	Roller pitch circle diameter	width	$\phi La$	na	$\phi Li$	ni	axial	radial	Kp	Kop	Kr
			Д:	Д:	dp	Б:					Ca	C0a	Kp	Kop	Kr
			мм	мм	мм	мм					кН	кН	кН	кН	кН
XU050077	40	112	77	22	97	6- $\phi$ 6.6	56	6-M8	22.4	29	14.3	14.2	1.4		
XU060094	57	140	94	26	120	6- $\phi$ 9	70	6-M8	32.5	37.5	20.7	18.4	2.4		
XU060111	76.2	145.79	111	15.87	133.1	8- $\phi$ 6.9	88.9	8- $\phi$ 6.9	36	44.5	22.8	21.5	1.2		
XU080120	69	170	120	30	148	6- $\phi$ 9	90	6-M8	56	53	35.5	26	4		
XU080149	101.6	196.85	149.6	22.22	177.8	16- $\phi$ 6.9	115.8	16- $\phi$ 6.9	63	66	40	32.5	3.6		
XU120179	124.5	234	179	35	214	12- $\phi$ 11	144.5	12- $\phi$ 11	118	179	75	88	7		
XU120222	140	300	222	36	270	12-M16	170	12- $\phi$ 18	133	275	85	131	12		
XU160260	191	329	260	46	305	20- $\phi$ 14	215	20- $\phi$ 14	212	350	135	173	16		
XU080264	215.9	311	264	25.4	295.3	12- $\phi$ 8.7	231.8	12- $\phi$ 8.7	85	117	54	57	6.9		
XU160405	336	474	405	46	450	30- $\phi$ 14	360	30- $\phi$ 14	270	550	172	270	25		
XU080430	380	480	430	26	462	20- $\phi$ 9	398	20-M10	110	280	70	138	12		
XU300515	384	646	515	86	598	18- $\phi$ 26	432	18- $\phi$ 26	720	1370	455	670	115		