

Double-row taper roller bearings with flanged outer ring

| Выбрать | запрос | Bearing designation | Размеры (мм) | | | | | | | | | | | Load factor | | | Load ratings(N) | | Limiting rotational speed. min-1 | | Масса (кг) |
|-------------|---------|---------------------|--------------|--------|-------|------|-------|------|-----|-----|---------|-------|------|-------------|--------|---------|-----------------|------|----------------------------------|-------|------------|
| | | | д: | Д: | Д1 | Т | Т1 | Б: | С | С1 | Г (мин) | r2min | e | Y1 | Y2 | Y0 | Кр | Кор | Смазка | Масло | |
| 2697709А | 45 | 75 | 81 | 77.588 | 9 | 20 | 69 | 4.95 | 1 | 0.3 | 0.39 | 1.72 | 2.56 | 1.68 | 107000 | 177000 | | 5000 | 1.078 | | |
| 697510АШ2 | 50 | 90 | 100 | 54.625 | 10.8 | 23 | 45 | 6 | 1.5 | 0.5 | 0.42 | 1.6 | 2.39 | 1.57 | 157000 | 232000 | | 5600 | 1.432 | | |
| 697810ЛК** | 50* | 90* | 94.76 | 64 | 11.11 | 29 | 51.3 | 4.76 | 2 | 0.3 | 0.3 | 2.23 | 3.32 | 2.18 | 125000 | 168000 | | 3200 | 1.643 | | |
| 697711ЛКУ** | 55* | 100* | 104.5 | 65 | 10 | 29.5 | 54 | 4.5 | 2 | 0.3 | 0.34 | 2 | 2.99 | 1.96 | 152000 | 224000 | | 3200 | 2.05 | | |
| 697712Л** | 60 | 100 | 104.5 | 58 | 10 | 26.5 | 47 | 4.7 | 1.3 | 0.3 | 0.35 | 1.95 | 2.9 | 1.9 | 138000 | 200000 | | 3200 | 1.69 | | |
| 697814Л** | 70 | 120 | 125.55 | 71.24 | 11.11 | 32 | 59.88 | 5.55 | 1.8 | 0.5 | 0.3 | 2.23 | 3.32 | 2.18 | 200000 | 315000 | | 3200 | 3.612 | | |
| 697815Л** | 75 | 130 | 136 | 79 | 12 | 37 | 66 | 5.5 | 1.8 | 0.5 | 0.22 | 3.07 | 4.57 | 3 | 268000 | 412000 | | 2400 | 4.015 | | |
| 697716Л** | 80 | 140 | 147 | 85 | 13.93 | 38.5 | 69.14 | 6.2 | 2.3 | 0.5 | 0.24 | 2.76 | 4.11 | 2.7 | 268000 | 434000 | | 2800 | 5.11 | | |
| 697817Л** | 85 | 140 | 146.34 | 85 | 14.28 | 38.5 | 69.14 | 6.35 | 2.3 | 0.5 | 0.24 | 2.76 | 4.11 | 2.7 | 268000 | 434000 | | 2700 | 4.725 | | |
| 697920Л1У** | 98.425 | 152.4 | 159.34 | 92 | 15 | 42 | 76 | 7.3 | 0.7 | 0.5 | 0.25 | 2.71 | 4.04 | 2.65 | 327000 | 545000 | | 2400 | 5.49 | | |
| 697724Л1** | 120 | 180 | 188 | 96.8 | 15.15 | 44 | 80.5 | 7 | 2.5 | 0.6 | 0.3 | 2.28 | 3.39 | 2.23 | 364000 | 668000 | | 2000 | 8 | | |
| 697824Л** | 120 | 190 | 198 | 108 | 17.6 | 50 | 88.8 | 8 | 2.5 | 0.6 | 0.27 | 2.54 | 3.74 | 2.45 | 450000 | 807000 | | 2000 | 10.5 | | |
| 697924У** | 120 | 200 | 208 | 84.05 | 19.86 | 38 | 64 | 10 | 2.3 | 0.3 | 0.46 | 1.47 | 2.19 | 1.44 | 417000 | 815000 | | 2000 | 10.044 | | |
| 697725Л** | 127* | 215.9* | 224 | 110 | 17 | 47 | 92 | 8 | 2.5 | 1 | 0.22 | 3.07 | 4.57 | 3 | 490000 | 926000 | | 1800 | 14.3 | | |
| 697927Л** | 133.35* | 196.85* | 204 | 92 | 18 | 38 | 76 | 10 | 2.5 | 0.6 | 0.33 | 2.04 | 3.04 | 1.99 | 261000 | 574000 | | 1800 | 8.393 | | |
| 697828Л** | 140 | 190 | 198 | 87 | 12.7 | 38 | 73 | 5.9 | 2 | 0.5 | 0.33 | 2.04 | 3.04 | 2 | 261000 | 574000 | | 2000 | 6.88 | | |
| 697928Л1** | 140 | 210 | 218 | 100 | 15 | 46 | 84 | 7 | 2.3 | 0.7 | 0.22 | 3.07 | 4.57 | 3 | 489000 | 923000 | | 2000 | 11.25 | | |
| 697732Л** | 160 | 240 | 248 | 110 | 17 | 50 | 92 | 8 | 2.5 | 0.9 | 0.25 | 2.69 | 4 | 2.63 | 544000 | 1110000 | | 1600 | 16.4 | | |
| 697737Л** | 185 | 235 | 243 | 85 | 14 | 37 | 70 | 6.55 | 2 | 0.5 | 0.22 | 3.11 | 4.64 | 3.04 | 337000 | 725000 | | 1600 | 7.92 | | |
| 697837Л | 185 | 240 | 248 | 84.9 | 14 | 37 | 70 | 6.55 | 2 | 0.5 | 0.22 | 3.11 | 4.64 | 3.04 | 338000 | 727000 | | 1200 | 8.684 | | |
| 697838Л** | 190 | 290 | 304 | 130 | 23 | 52 | 108 | 12 | 2.5 | 0.9 | 0.38 | 1.78 | 2.65 | 1.74 | 697000 | 1310000 | | 1300 | 28.04 | | |
| 697847Л | 234.95* | 327.025* | 336.55 | 122 | 25.4 | 61 | 90.24 | 9.52 | 6 | 1.5 | 0.33 | 2.03 | 3.02 | 1.98 | 720000 | 1700000 | | 1500 | 28.690 | | |
| 697848ЛУ** | 240 | 320 | 334 | 128.8 | 19.5 | 56 | 107 | 9 | 3 | 0.5 | 0.33 | 2.03 | 3.02 | 1.98 | 721000 | 1740000 | | 1000 | 26.95 | | |