


4200 Series Double row angular contact ball bearing



Выбрать запрос	Подшипник №.	Граничные размеры (мм)					Грузоподъемность (кН)			Предельная скорость (об / Масса мин)		
		д:	Д:	Б:	рупий мин.	Динамический (Cr)	Статический (Cor)	Смазка	Масло	Кг		
4200	10	30	14	0.6	7.7	5.9	18000	22000	0.057			
4201	12	32	14	0.6	7.75	6.15	17000	20000	0.062			
4202	15	35	14	0.6	9.75	9	14000	17000	0.071			
4203	17	40	16	0.6	11.7	10.4	12000	15000	0.106			
4204	20	47	18	1	16.4	12.5	10000	13000	0.165			
4205	25	52	18	1	19	14.6	9000	11000	0.189			
4206	30	62	20	1	26	20.8	8000	9500	0.298			
4207	35	72	23	1.1	35.1	28.5	6700	8000	0.46			
4208	40	80	23	1.1	37.1	32.5	6000	7000	0.558			
4209	45	85	23	1.1	39	36	5600	6700	0.605			
4210	50	90	23	1.1	41	40	5000	6000	0.651			
4211	55	100	25	1.5	44.9	44	4800	5600	0.882			
4212	60	110	28	1.5	57.2	55	4500	5300	1.2			
4213	65	120	31	1.5	67.6	67	4000	4800	1.45			
4214	70	125	31	1.5	70.2	73.5	3600	4300	1.5			
4215	75	130	31	1.5	72.8	80	3400	4000	1.6			
4216	80	140	33	2	80.6	90	3200	3800	2			
4217	85	150	36	2	93.6	102	3000	3600	2.55			
4218	90	160	40	2	112	122	2800	3400	3.2			
4220	100	180	46	2.1	14	15.6	2400	3000	4.7			