


CSF crossed roller Bearing



Выбрать	Обозначение запрос	Размеры (в/л)													Номинальная основная нагрузка (кН)		Масса (кг)
		Подшипник	д:	Д:	Т	Д1	Д2	Д21	ДЗ	n1-d1	n2-d2	n21-d21	n3-d3	д31	т31	рупий мин.	
CSF14-3516	9	55	16.5	49	23	14.5	15.5	8-φ3.5	6-M4	6-M3	2-φ3	---	---	0.3 x 45 °	4.6	5.1	0.25
CSF17-4216	10	62	16.5	56	27	17.5	17.5	10-φ3.5	6-M5	6-M4	2-φ3	---	---	0.3 x 45 °	5.2	6.4	0.27
CSF20-5016	14	70	16.5	64	32	24	19	12-φ3.5	8-M6	8-M5	4-φ3	4-φ2.8	7	0.3 x 45 °	6.1	8.4	0.36
CSF25-6218	20	85	18.5	79	42	30	26	16-φ3.5	8-M8	8-M6	4-φ3	4-φ2.8	7	0.5 x 45 °	11.2	16	0.65
CSF32-8022	26	112	22.5	104	55	40	34	16-φ4.5	8-M10	8-M8	4-φ5	4-φ4.7	10	0.5 x 45 °	18.5	28.3	1.1
CSF40-9524	24	126	24	117	68	50	42	20-φ5	8-M10	8-M8	4-φ5	---	---	0.5 x 45 °	18.9	30.7	1.6
CSF50-12031	32	157	31	147	84	60	50	16-φ5.5	8-M14	8-M14	4-φ5	---	---	0.5 x 45 °	42.8	67.7	3.6
CSF65-16039	44	210	39	198	110	80	64	20-φ6.5	8-M16	8-M16	4-φ6	---	---	0.5 x 45 °	67.7	114.9	7.8